Revision Date 12.08.2015

Print Date 13.08.2015

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	: Shell Alexia 50
Product code	: 001A0095

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Engine oil.
Uses advised against	:	This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Shell UK Oil Products Limited Shell Centre London SE1 7NA United Kingdom
Telephone Telefax Email Contact for Safety Data Sheet	<ul> <li>: (+44) 08007318888</li> <li>: If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com</li> </ul>

## 1.4 Emergency telephone number

: +44-(0) 151-350-4595

#### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

## 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms		>
Signal word	: Warning	
Hazard statements	:	PHYSICAL HAZARDS:

	Davisian Data	40.00.0045	
Version 4.2	Revision Date	12.08.2015	Print Date 13.08.2015
	H317	Not classified as a according to CLP of HEALTH HAZARD May cause an aller ENVIRONMENTAI Not classified as er according to CLP of	riteria. S: rgic skin reaction. L HAZARDS: nvironmental hazard
Precautionary statements	Prevention: P280	Wear protective glo eye protection/ fac	oves/ protective clothing/ e protection.
	<b>Response:</b> P302 + P352	IF ON SKIN: Wash soap.	with plenty of water and
	P333 + P313	•	ash occurs: Get medical
	Storage:	No precautionary p	ohrases.
	<b>Disposal:</b> P501	Dispose of content approved waste dis	s/ container to an

Hazardous components which must be listed on the label: Contains calcium sulphonate.

#### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature	<ul> <li>Highly refined mineral oils and additives. The highly refined mineral oil contains &lt;3% (w/w) DMSO- extract, according to IP346.</li> </ul>
	<ul> <li>* contains one or more of the following CAS-numbers (REACH registration numbers): 64742-53-6 (01-2119480375- 34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01- 2119487077-29), 64742-56-9 (01-2119480132-48), 64742-65- 0 (01-2119471299-27), 68037-01-4 (01-2119486452-34), 72623-86-0 (01-2119474878-16), 72623-87-1 (01- 2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69- 9 (01-0000020163-82).</li> </ul>

Version 4.2

Revision Date 12.08.2015

Print Date 13.08.2015

## Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Sulphurised calcium phenate	90480-91-4 291-829-9	Aquatic Chronic4; H413	< 10
Calcium long chain alkaryl sulphonate	722503-68-6	Skin Sens.1; H317 Aquatic Chronic4; H413	< 3
Polyolefin amide alkeneamine		Aquatic Chronic4; H413	< 3
Alkylphenol	310-154-3	Skin Irrit.2; H315 Eye Irrit.2; H319 Repr.1A; H360 Aquatic Acute1; H400 Aquatic Chronic1; H410	< 1.5
Calcium long chain alkaryl sulphonate		Aquatic Chronic4; H413	< 3
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Asp. Tox.1; H304	0 - 90

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.	
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.	
In case of skin contact	<ul> <li>Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.</li> <li>If persistent irritation occurs, obtain medical attention.</li> </ul>	
In case of eye contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.	
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.	
4.2 Most important symptoms and effects, both acute and delayed		

Symptoms	: Skin sensitisation (allergic skin reaction) signs and symptoms

Unsuitable extinguishing

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
	may include itching and/or a rash. Oil acne/folliculitis signs and symptor of black pustules and spots on the sk Ingestion may result in nausea, vomi	in of exposed areas.
4.3 Indication of any immediate r	nedical attention and special treatment	t needed
Treatment : Notes to doctor/physician: Treat symptomatically.		
SECTION 5: Firefighting meas	sures	
5.1 Extinguishing media		
Suitable extinguishing media	: Foam, water spray or fog. Dry chemic dioxide, sand or earth may be used for	

#### media 5.2 Special hazards arising from the substance or mixture

one opeonal nazarao anomg nem	
Specific hazards during firefighting	<ul> <li>Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.</li> </ul>
5.3 Advice for firefighters	
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

: Do not use water in a jet.

## **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: 6.1.1 For non emergency personnel:
	Avoid contact with skin and eyes.
	6.1.2 For emergency responders:
	Avoid contact with skin and eyes.

## **6.2 Environmental precautions**

	Environmental precautions	: Use appropriate containment to avoid environmental
--	---------------------------	--

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
	contamination. Prevent from spreading or ditches or rivers by using sand, earth, or or barriers.	<b>e</b>
	Local authorities should be advised if signi cannot be contained.	ficant spillages
6.3 Methods and materials for cont	ainment and cleaning up	
Methods for cleaning up	<ul> <li>Slippery when spilt. Avoid accidents, Prevent from spreading by making a bound of the containment material. Reclaim liquid directly or in an absorb Soak up residue with an absorbent subsuitable material and dispose of properties.</li> </ul>	ent. ich as clay, sand or other

## 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

## **SECTION 7: Handling and storage**

General Precautions :	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
7.1 Precautions for safe handling	
Advice on safe handling :	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Product Transfer :	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
7.2 Conditions for safe storage, inc	luding any incompatibilities
Other data :	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
	Store at ambient temperature.
	Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
5 / 40	800004.004

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
	The storage of this product may be s Pollution (Oil Storage) (England) Reg guidance may be obtained from the l agency office.	gulations. Further
Packaging material	: Suitable material: For containers or or steel or high density polyethylene. Unsuitable material: PVC.	container linings, use mild
Container Advice	: Polyethylene containers should not b temperatures because of possible ris	
7.3 Specific end use(s)		
Specific use(s)	: Not applicable	

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral		TWA	5 mg/m3	US. ACGIH Threshold Limit Values

## **Biological occupational exposure limits**

No biological limit allocated.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Version 4.2

Revision Date 12.08.2015

Print Date 13.08.2015

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### 8.2 Exposure controls

Engineering measures The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection	<ul> <li>If material is handled such that it could be splashed into eyes, protective eyewear is recommended.</li> <li>Approved to EU Standard EN166.</li> </ul>
Hand protection	
Remarks	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand

care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.         For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-tern/splash protection we recommend the same, but recognize that suitable gloves glores can be identified. For may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.         Skin and body protection       : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.         Respiratory protection       : No respiratory protection is ordinarily required under normal conditions of use.         In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protect equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combined particulate/organic gases and vapours [Type A/Type P boling point > 65°C (149°F)] meeting EN14387 and EN1438.         Thermal hazards       : Not applicable         Hygiene measures       : Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "C	sion 4.2	Revision Date 12.08.2015	Print Date 13.08.20
breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.Skin and body protection:Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.Respiratory protection:No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable of the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suitable of the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suitable of the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suitable of the specific conditions of use and meeting respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.Thermal hazards:Exposure to this p		care. Gloves must only be worn or gloves, hands should be washed a	n clean hands. After using and dried thoroughly.
risk of splashing, also wear an apron.         Respiratory protection       : No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.         Thermal hazards       : Not applicable         Hygiene measures       : Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".         Environmental exposure controls       : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in		breakthrough time of more than 24 for > 480 minutes where suitable g short-term/splash protection we re recognize that suitable gloves offe may not be available and in this ca time maybe acceptable so long as and replacement regimes are follo a good predictor of glove resistant dependent on the exact composition Glove thickness should be typically	10 minutes with preference gloves can be identified. For commend the same, but ring this level of protection ase a lower breakthrough appropriate maintenance wed. Glove thickness is not ce to a chemical as it is on of the glove material. y greater than 0.35 mm
conditions of use.       In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.         Thermal hazards       : Not applicable         Hygiene measures       : Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".         Environmental exposure controls       : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in	Skin and body protection		
Hygiene measures       : Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".         Environmental exposure controls       : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in	Respiratory protection	conditions of use. In accordance with good industrial precautions should be taken to ave If engineering controls do not main concentrations to a level which is a health, select respiratory protection specific conditions of use and mee Check with respiratory protective e Where air-filtering respirators are s appropriate combination of mask a Select a filter suitable for combined and vapours [Type A/Type P boiling	hygiene practices, oid breathing of material. ntain airborne adequate to protect worker n equipment suitable for the eting relevant legislation. equipment suppliers. suitable, select an and filter. d particulate/organic gases
reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".         Environmental exposure controls         General advice       : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in	Thermal hazards	: Not applicable	
General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in	Hygiene measures	reasonably practicable. Reference Health and Safety Executive's pub	should be made to the
relevant environmental protection legislation. Avoid contamination of the environment by following advice given in	Environmental exposure c	ontrols	
being discharged to waste water. Waste water should be	General advice	relevant environmental protection contamination of the environment Chapter 6. If necessary, prevent u	legislation. Avoid by following advice given in undissolved material from

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
	treated in a municipal or industrial or before discharge to surface water. Local guidelines on emission limits must be observed for the discharge vapour.	for volatile substances

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical	aı	nd chemical properties
Appearance	:	Liquid at room temperature.
Colour	:	amber
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рH	:	Not applicable
pour point	:	<= -6 °CMethod: ASTM D97
Initial boiling point and boiling range	:	> 280 °Cestimated value(s)
Flash point	:	>= 205 °C Method: ASTM D93 (PMCC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit	:	Typical 10 %(V)
Lower explosion limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C) estimated value(s)
Relative vapour density	:	> 1estimated value(s)
Relative density	:	0.932 (15 °C)
Density	:	932 kg/m3 (15.0 °C) Method: ASTM D4052
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n-	:	Pow: > 6(based on information on similar products)

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
octanol/water		
Auto-ignition temperature	: > 320 °C	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 225 mm2/s (40.0 °C) Method: ASTM D445	
	19.5 mm2/s (100 °C) Method: ASTM D445	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	
9.2 Other information		
Conductivity	: This material is not expected to be a	static accumulator.

,	
Decomposition temperature	: Data not available

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

# 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

# 10.3 Possibility of hazardous reactions

: Reacts with strong oxidising agents.
: Extremes of temperature and direct sunlight.
: Strong oxidising agents.
products
: Hazardous decomposition products are not expected to form during normal storage.

Revision Date 12.08.2015

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	f:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.
Acute dermal toxicity	:	LD50 Rabbit: > 5,000 mg/kg Remarks: Expected to be of low toxicity:

#### Skin corrosion/irritation

#### Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Expected to be slightly irritating.

#### Respiratory or skin sensitisation

#### Product:

Remarks: For skin sensitisation:, Expected to be a skin sensitizer.

Remarks: For respiratory sensitisation:, Not expected to be a sensitiser.

#### **Components:**

#### Calcium long chain alkaryl sulphonate:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Revision Date 12.08.2015

Print Date 13.08.2015

#### Germ cell mutagenicity

#### Product:

: Remarks: Not considered a mutagenic hazard.

#### Carcinogenicity

## Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

#### **Reproductive toxicity**

#### Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

#### STOT - single exposure

#### Product:

Remarks: Not expected to be a hazard.

#### STOT - repeated exposure

#### Product:

Remarks: Not expected to be a hazard.

#### Aspiration toxicity

#### Product:

Not considered an aspiration hazard.

## **Further information**

#### Product:

12/19

800001001344 GB

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
concentration of such	may contain harmful impurities that have accumulan n impurities will depend on use and they may pres osal., ALL used oil should be handled with caution	sent risks to health and the
Remarks: Continuou	s contact with used engine oils has caused skin ca	ancer in animal tests.
Remarks: Slightly irri	tating to respiratory system.	
Remarks: Classificat	ions by other authorities under varying regulatory	frameworks may exist.
Summary on evalua Germ cell mutagenic	ation of the CMR properties ity- : This product does not meet the crite	eria for classification in

: This product does not meet the criteria for classification in

: This product does not meet the criteria for classification in

categories 1A/1B.

categories 1A/1B.

categories 1A/1B.

# SECTION 12: Ecological information

## 12.1 Toxicity

Assessment

Assessment

Assessment

Carcinogenicity -

Reproductive toxicity -

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).Test data for additive packages has also been used in the classification of this product. Based on available data, the classification criteria are not met.
Product:		
Toxicity to fish (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to crustacean (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l

Shell Alexia 50		
Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
Toxicity to fish (Chronic	: Remarks: Data not available	
toxicity) Toxicity to crustacean	: Remarks: Data not available	
(Chronic toxicity) Toxicity to microorganisms		
(Acute toxicity)	Remarks: Data not available	
12.2 Persistence and degradab	ility	
Product:		
Biodegradability	: Remarks: Expected to be not read constituents are expected to be in contains components that may pe	herently biodegradable, but
12.3 Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components v bioaccumulate.	with the potential to
Partition coefficient: n- octanol/water	: Pow: > 6Remarks: (based on info	rmation on similar products)
12.4 Mobility in soil		
Product:		
Mobility	<ul> <li>Remarks: Liquid under most envir enters soil, it will adsorb to soil pa mobile.</li> <li>Remarks: Floats on water.</li> </ul>	
12.5 Results of PBT and vPvB a	assessment	
Product:		
Assessment	: This mixture does not contain any substances that are assessed to l	
12.6 Other adverse effects		
Product:		
Additional ecological information	<ul> <li>Product is a mixture of non-volatil expected to be released to air in a Not expected to have ozone deple photochemical ozone creation pot potential.</li> </ul>	any significant quantities., etion potential,
	Poorly soluble mixture., May caus organisms.	e physical fouling of aquatic

Revision Date 12.08.2015

# **SECTION 13: Disposal considerations**

13.1 Waste treatment methods	
Product	<ul> <li>Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.</li> <li>Waste, spills or used product is dangerous waste.</li> </ul>
	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Waste catalogue	: EU Waste Disposal Code (EWC):
Waste Code	: 13 02 05*
Remarks	: Classification of waste is always the responsibility of the end user.
	Hazardous Waste (England and Wales) Regulations 2005.

## **SECTION 14: Transport information**

14.1 UN number	
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
ΙΑΤΑ	: Not regulated as a dangerous good
14.2 Proper shipping name	
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
ΙΑΤΑ	: Not regulated as a dangerous good
14.3 Transport hazard class	

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.5 Environmental hazards		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
14.6 Special precautions for us	ser	
Remarks	: Special Precautions: Refer to Chapter for special precautions which a user ne needs to comply with in connection with	eds to be aware of or
14.7 Transport in bulk according	ng to Annex II of MARPOL 73/78 and the IB	C Code
Pollution category	: Not applicable	
Ship type	: Not applicable	
Product name	: Not applicable	
Special precautions	: Not applicable	
Additional Information	: MARPOL Annex 1 rules apply for bulk	shipments by sea.

# **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

roarcey, nearth and environmen	ital regulations/legislation	specific for the substance of mixtur
REACH - List of substances subj (Annex XIV)	ject to authorisation :	Product is not subject to Authorisation under REACH.
Volatile organic compounds :	0 %	
Other regulations :	Safety at Work etc. Act 19 Pollution Prevention and 1995. Factories Act 1961, and Use of Transportable Regulations 2011. Chemi Packaging for Supply) Re Substances Hazardous to amended). Merchant Ship Pollutants) Regulations 19 and Dangerous Occurren	Act 1990 (as amended). Health and 974. Consumers Protection Act 1987. Control Act 1999. Environment Act . The Carriage of Dangerous Goods Pressure Equipment (Amendment) cals (Hazard Information and egulations 2009. Control of b Health Regulations 2002 (as oping (Dangerous Goods and Marine 997. Reporting of Injuries, Diseases ces Regulations 1995 (as amended). oment Regulations 2002. Personal

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
	Protective Equipment at Work Regu Waste (England and Wales) Regula Control of Major Accident Hazards F amended). Renewable Transport Fu (as amended). Energy Act 2011. En (England and Wales) Regulations 2 (England and Wales) Regulations 2 Planning (Hazardous Substances) A regulations. The Environmental Pro Ozone-Depleting Substances) Regu	tions 2005(as amended). Regulations 1999 (as uel Obligations Order 2007 wironmental Permitting 010 (as amended). Waste 011 (as amended). Act 1990 and associated tection (Controls on

#### The components of this product are reported in the following inventories:

EINECS	: All components listed or polymer exemp	ot.
TSCA	: All components listed.	

## 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## **SECTION 16: Other information**

REGULATION (EC) No 1272/2008	<b>Classification procedure:</b>
Skin sensitisation, Category 1, H317	Expert judgement and weight of evidence
	determination.

#### Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

## Full text of other abbreviations

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
Abbreviations and Acro	nyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015		
	ADR = European Agreement concer	ning the International		
	Carriage of Dangerous Goods by Ro			
		AICS = Australian Inventory of Chemical Substances		
	ASTM = American Society for Testing and Materials			
	BEL = Biological exposure limits			
	BTEX = Benzene, Toluene, Ethylbenzene, Xylenes			
	CAS = Chemical Abstracts Service	-		
	CEFIC = European Chemical Industry Council			
	CLP = Classification Packaging and Labelling			
	COC = Cleveland Open-Cup			
	DIN = Deutsches Institut fur Normun	Ig		
	DMEL = Derived Minimal Effect Leve	el		
	DNEL = Derived No Effect Level			
	DSL = Canada Domestic Substance	List		
	EC = European Commission			
	EC50 = Effective Concentration fifty			
	ECETOC = European Center on Eco	otoxicology and		
	Toxicology Of Chemicals			
	ECHA = European Chemicals Agend			
	EINECS = The European Inventory	of Existing Commercial		
	Chemical Substances			
	EL50 = Effective Loading fifty	Chamical Cubatanasa		
	ENCS = Japanese Existing and New	V Chemical Substances		
	Inventory			
	EWC = European Waste Code	of Classification and		
	GHS = Globally Harmonised System of Classification and			
	Labelling of Chemicals	earch on Cancer		
	IARC = International Agency for Research on Cancer IATA = International Air Transport Association			
	IC50 = Inhibitory Concentration fifty			
	IL50 = Inhibitory Level fifty			
	IMDG = International Maritime Dang	erous Goods		
	INV = Chinese Chemicals Inventory			
	IP346 = Institute of Petroleum test			
	determination of polycyclic aromatics			
	KECI = Korea Existing Chemicals In			
	LC50 = Lethal Concentration fifty			
	LD50 = Lethal Dose fifty per cent.			
	LL/EL/IL = Lethal Loading/Effective I	Loading/Inhibitory loading		
	LL50 = Lethal Loading fifty	5 , 5		
	MARPOL = International Conventior	n for the Prevention of		
	Pollution From Ships			
	NOEC/NOEL = No Observed Effect	Concentration / No		
	Observed Effect Level			
	OE_HPV = Occupational Exposure -			
	PBT = Persistent, Bioaccumulative and Toxic			
	PICCS = Philippine Inventory of Chemicals and Chemical			
	Substances			
	PNEC = Predicted No Effect Concer			
	REACH = Registration Evaluation A	nd Authorisation Of		
	Chemicals			
	RID = Regulations Relating to Intern	ational Carriage of		
	Dangerous Goods by Rail			

Version 4.2	Revision Date 12.08.2015	Print Date 13.08.2015
	SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative	
Further information		
Other information	: A vertical bar () in the left margin indicates an amendment from the previous version.	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.